



WWW.DAVIDCLARK.COM

## DC JET-X Aviation Headset

Dual Ear, Dual Plugs

P/N 43107G-01

Data Sheet



DC JET-X Headset

### FEATURES AND BENEFITS

- Adjustable suspension assembly for personalized fit
- Swivel hinge stirrups for secure, comfortable fit
- Fail-Safe Operation - Ensures full communication in the event of battery loss or system failure
- Enhanced Auto Shut-off – Prevents accidental loss of battery power

- Full flex boom for precise microphone placement
- Fold-flat design for compact storage in David Clark branded headset bag (included)
- Three-year warranty
- TSO-C139a Approved

### TECHNICAL DATA

Ear Coupling	On-The-Ear
Hardware	Acetal Copolymer
Connector Type	Standard Dual GA Plug
Connection Cable	0.118" (3- mm) O.D. shielded cable, Length ~6.3 ft. (1.92 m)
Dome Type	ABS
Contact Pressure	0.3 lb. (1.3 N)
Transducer Principle	Dynamic
H/S Impedance	600Ω Mono +/- 20%
H/S Frequency Response	30 - 15 kHz
Characteristic SPL	91 dB SPL (1 kHz, 1 mW) @ maximum volume nominal
Total Harmonic Distortion (THD)	< 3% - 110 dB SPL (300 - 3,000 Hz)
ENC Attenuation Range	100 Hz - 8 kHz
ENC Peak Attenuation	>15 dB @ 500 Hz nominal
Microphone Principle	Pre-polarized condenser microphone (electret), noise cancelling
Microphone Impedance	150Ω nominal
Microphone Sensitivity	400mV +/- 6 dB into 150Ω load @1 kHz for 114 dB SPL input
Microphone Frequency Response	150 Hz – 8 kHz
Microphone DC Supply Voltage	8 - 16 Volts, not polarity sensitive
Source Resistance	470Ω
Operating Voltage	1.5VDC (1xAA)
Operating Temperature	-20°C to +55°C
Weight (w/o Cable)	4.5 oz. (127.6 g)

360 Franklin Street, Box 15054, Worcester, MA 01615-0054 • Tel: 800-298-6235 • Fax: 508-753-5827

• Email: sales@davidclark.com • Web site: www.davidclark.com

Technical data subject to change without prior notice.  
Current data available at www.davidclark.com

